

OSCILLATING EDGE SANDER

60" & 80" MODELS

When you choose the Wil-Be Oscillating Edge Sander, you choose sturdiness and reliability. Whichever model you opt for, you are assured to get a quality machine designed especially for intensive industrial use.



60" model shown here
with the auxiliary table
available in option

STANDARD FEATURES

- Height adjustable and tiltable front table.
- Sanding belt backed up by a cast-iron precision platen.
- Sanding belt motor totally enclosed and fan cooled.
- Oscillation mechanism on ball bearings.
- Safety guard on driving roller with dust collection port.

OPTIONS

- Height adjustable and tiltable auxiliary table.
- Additional table and platen at the back of the machine.
- Graphite sheet on platen.

SPECIFICATIONS

- Sanding belt motor: 7.5 hp, 1800 rpm, 550 volts, 3 phases.
- Oscillation motor: 0.75 hp, with speed reducer, 550 volts, 3 phases.
- Sanding belt size: 8" x 162" or 8" x 206" depending of model.
- Platen height: 9¼".
- Front table size: 10" x 60" or 10" x 80" depending of model.
- Optional auxiliary table size: 12" x 24½".
- Dust collection port diameter: 5".
- Approximate overall dimensions and weight:
 - 60" model: 29" x 87" x 50" high, 1600 lbs
 - 80" model: 29" x 103" x 50" high, 1950 lbs

Machine entirely adjusted and tested at the plant before shipping.
Warranty: 1 year on parts and labour, 90 days on electrical components.

If this product interests you but that its capacities do not fully meet your requirements, please contact us.